

S-Series Helical-Worm Gearmotors


SEW-Eurodrive's S-Series right angle gearmotors offer helical-worm gearing that combines durability with exceptional performance in a compact design. Its helical input stage provides greater efficiency than a single stage worm unit. An additional helical gear unit added to the input enables very large ratios.

Product Range

- Power ratings from 0.05 to 46 HP
- Ratios from 3.97 to 33,818
- Output torques to 35,400 lb-in

Reducer

- Efficiency up to 94%, depending on ratio
- Worm shaft and helical gears manufactured from certified steel, heat treated to a case hardness of 58-62 Rockwell C for infinite fatigue strength
- Gears are milled, hardened and ground to assure minimum noise, minimum heat, and maximum efficiency
- Torque rating based upon mechanical capacity under continuous duty operation
- Gearcases made of high strength gray cast iron, SAE Class 30 or equivalent (GG20)
- Anti-friction bearings for optimum load capacity and long life
- Captured keys on input and output shafts
- O-ring on flange to prevent oil leakage when mounted on a surface that is not totally flat
- High cross-section modulus design, rugged monobloc design for maximum rigidity
- Center tapped holes on output shafts to aid the installation of shaft components
- Exclusive interlocking 2-piece seal design consisting of a patented bi-helix FKM inner seal and a double-lip Nitrile (Buna N) outer seal – provides three sealing surfaces against contaminants
- Metric or Inch dimension output shaft
- Removable inspection cover
- Shock capacity meets or exceeds AGMA 6009-A00



Motor

- Inverter duty
- Connection terminals
- Low rotor inertia for high cycling and tight control
- EISA (IE3) "Premium" available
- 50Hz, 60Hz, or 50/60Hz global motor
- **CE** for shipment into Europe

Mounting

- Torque arm for shaft mounting
- B14 or B5 flange with centering tenon
- Foot mounting
- Can be ordered for any mounting orientation

Optional Features

- C-Face or IEC motor adapter
- TorqLOC® taper hollow shaft
- Corrosion and/or long term storage protection
- FKM seals instead of NBR
- High cycling fail-safe brake
- Forced cooling fan for low frequency operation
- Thermostat or thermistor protection
- Plug connectors for quick motor replacement
- Two-speed motor
- Motor encoder - built-in or externally mounted
- CSA hazardous location and ATEX rated motors
- Servo Motor



U.S. Operations:

Midwest Region

SEW-Eurodrive, Inc.
2001 West Main Street
Troy, OH 45373
Telephone: (937) 335-0036
Fax: (937) 332-0038
cstroy@seweurodrive.com

Northeast Region

SEW-Eurodrive, Inc.
2107 High Hill Road
Bridgeport, NJ 08014
Telephone: (856) 467-2277
Fax: (856) 845-3179
csbridgeport@seweurodrive.com

Southeast Region

SEW-Eurodrive, Inc.
1295 Old Spartanburg Hwy.
Lyman, SC 29365
Telephone: (864) 439-7537
Fax: (864) 439-7830
cslyman@seweurodrive.com

Southwest Region

SEW-Eurodrive, Inc.
3950 Platinum Way
Dallas, TX 75237
Telephone: (214) 330-4824
Fax: (214) 330-4724
csdallas@seweurodrive.com

Western Region

SEW-Eurodrive, Inc.
30599 San Antonio Street
Hayward, CA 94544
Telephone: (510) 487-3560
Fax: (510) 487-6433
cshayward@seweurodrive.com

www.seweurodrive.com

About SEW-Eurodrive

Our product is motion. Our focus is solutions. As a worldwide supplier of innovative gearing, motor, and electronic drive technology, we have been solving problems in large and small applications within virtually every industry for over 80 years.

We also specialize in reducing the total cost of ownership with our customer-specific energy saving solutions.

Globally, we have assembly centers in 44 countries, along with 15 production plants. Therefore, we are able to provide uniform quality standards and international application experience.

Locally, we provide final assembly and custom modifications plus assistance with project planning, startup, and training. All products are backed by our industry-leading 24/7 support program.

SEW-Eurodrive ... Driving the World

